



PDM Series



PICOQUANT

Single Photon Avalanche Diodes



- Timing resolution down to 50 ps (FWHM)
- Quantum efficiency 49 % at 550 nm
- Different detector diameters: 20, 50 and 100 μm
- Ultra stable at high count rates
- Low power consumption



Applications

- Time-resolved fluorescence spectroscopy
- Single Molecule Spectroscopy (SMS)
- Fluorescence Lifetime Imaging (FLIM)
- Fluorescence Correlation Spectroscopy (FCS)
- Fast laser measurement and calibration
- LIDAR, Ranging, ...
- Dynamic light scattering, particle sizing
- Quantum optics


Single Photon Avalanche Diodes

The photon counting detector modules of the PDM Series are all solid-state instruments designed and manufactured by Micro Photon Devices (MPD) of Bolzano, Italy. They have photon detection efficiency of 49 % at 550 nm and generate a TTL output pulse per detected photon. With fast-timing option (additional circuit board installed inside) they provide better than 50 ps FWHM photon timing resolution for a wide range of wavelengths. The excellent photon detection efficiency and superior timing resolution is obtained through the use of epitaxial silicon Single Photon Avalanche Diodes (SPAD) and patented integrated Active Quenching Circuits (iAQC), specifically designed and optimized for time-resolved photon counting applications.

The SPADs are available with a diameter of the active area of 20, 50 or 100 μm . They cover a spectral range from about 400 nm to 900 nm with the highest quantum efficiency in the VIS range around 550 nm. They are extremely robust and can withstand continuous exposition to daylight. Their superior timing makes them a real alternative to photomultiplier tubes for many applications. Especially above 470 nm, the temporal response is even comparable to MCP-PMTs. Moreover, the high quantum efficiency makes them an ideal detector for single molecule applications, like Fluorescence Correlation Spectroscopy (FCS) or Fluorescence Lifetime Imaging (FLIM), especially as the SPAD has a stable timing even at count rates exceeding 1 million counts/sec.

Measurement Examples

Instrument Response Function (IRF) of a PDM module with an active area of 50 μm . The measurements were taken with the TCSPC module PicoHarp 300 and different laser heads of the LDH Series driven by the PDL 800-B.



Specifications (@ 25 °C and 5 V overvoltage)

Dark Counts (typical)	20 μm SPAD	50 μm SPAD	100 μm SPAD
Non-cooled version	< 250 cps	< 5.000 cps	< 20.000 cps
Cooled version	< 25 cps	< 50 cps	< 250 cps

Single Photon Timing Resolution

TTL counting output (FWHM)	250 ps
NIM timing output (FWHM) *	down to 50 ps, increases in blue/UV spectral range

Afterpulsing Probability < 3 % (typical)

Input/Output

Dead time	77 ns (typical)
Output signal	TTL for counting output, NIM for timing output *
Output pulse rise and fall times	< 2 ns on 10 pF load
Output pulse duration	20 ns (typical)
Gating input	TTL control (low level gates detector off)
Supply input connector	standard 3.5 mm supply socket

Supply Voltage unregulated DC, any value 5 V - 12 V

* Available as an option

Further available are Fluorescence Lifetime Spectrometers; Time-resolved Fluorescence Microscopes; Upgrade kit for Laser Scanning Microscopes; Picosecond/Nanosecond Pulsed, Modulated and Fast Switched Diode Lasers; PC Modules for TCSPC. Please call for detailed information and data sheets. **Please check our website for updated information.**

All Information given here is reliable to our best knowledge. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications and external appearances are subject to change without notice. Trademarks or corporate names are used for explanation and identification, to the owner's benefit and without intent to infringe.

© PicoQuant GmbH, February 2011



PicoQuant GmbH
Rudower Chaussee 29 (IGZ)
12489 Berlin
Germany

Phone +49-(0)30-6392-6929
Telefax +49-(0)30-6392-6561
Email info@picoquant.com
WWW http://www.picoquant.com