

# Prima NEW

## 3-color picosecond laser

- 3-color picosecond laser (450, 515, 640 nm)
- Compact, stand alone, affordable
- Pulsed and cw operation, fast cw switching
- Triggerable internally and externally, up to 200 MHz
- Fully computer controlled



### Applications

- Material science & chemical research
- Lifescience
- Photoluminescence lifetime and quantum yield measurements
- Fluorescence lifetime measurements
- Time-resolved microscopy & single molecule detection (FLIM, FRET, PIE-FRET, FCS)

Prima is a compact, stand-alone and affordable laser module offering 3 individual emission wavelengths that can be operated in picosecond pulsed and continuous wave (cw) mode. The picosecond pulses can be triggered either by the module's internal clock or by an external oscillator at up to 200 MHz. The module is fully computer controlled, making its operation very easy: Connect Prima to a PC via an USB port and all changes in operation parameters can be done via a convenient software interface.

### Specifications


Optical output			
Available wavelengths <sup>1</sup>	450 nm	515 nm	640 nm
Max. pulsed power <sup>2</sup>	10 mW	10 mW	10 mW
Pulse duration	< 120 ps	< 200 ps	< 150 ps
Max cw power	50 mW	50 mW	50 mW
Beam dimension <sup>3</sup>	0.55 ± 0.10 mm	0.60 ± 0.10 mm	0.8 ± 0.20 mm
Beam circularity	typ > 0.5	typ > 0.5	typ > 0.5
Polarization	typ. linear		
Polarization Extinction Ratio (PER)	typ. > 1:10 (> 10 dB)		
Spectral width FWHM (pulsed)	4 nm	6 nm	2 nm
Spectral width FWHM (CW)	< 1 nm		

Repetition rates	
<b>Internal</b>	
Range	User selectable 1 kHz to 200 MHz 1000 increments of 1 kHz from 1 to 999 kHz 200 increments of 1 MHz from 1 to 200 MHz
<b>External</b>	
Range	0 Hz to 200 MHz
Trigger level	-1V ... +5V into 50 Ohm
Jitter	< 20 ps
Connector	SMA
<b>Synchronization output</b>	
Amplitude	< -800 mV into 50 Ohm (NIM)
Connector	SMA
<b>Gating</b>	
Rise/Fall Time	< 3 ns
ON Time Gate	freely adjustable from < 10 ns to 1 ms
OFF Time Gate (as a factor of ON Time Gate)	freely adjustable from 1 to 255
Impedance	10 kOhms with pull-up 50 Ohms with pull-down
Connector	SMA
<b>Dimensions</b>	
Size (h × w × l)	75 × 83 × 140 mm
Weight	approx. 1 kg
<b>Operation</b>	
Temperature range	10 - 35 °C
Rel. humidity	< 80 % (non condensing)
Maximum power consumption	< 30 W
<b>Interface</b>	
PC interface	USB 2.0
Connector	USB-C
Operating system	Windows™ 10

<sup>1</sup> Typical value in pulsed mode. A slight shift to longer wavelengths in cw mode.

<sup>2</sup> This is the maximum average power at maximum intensity setting and max repetition rate. A pulse broadening up to 500 ps FWHM is possible at maximum intensity setting.

<sup>3</sup> Measured at 1 m distance from laser aperture



PicoQuant GmbH  
Rudower Chaussee 29 (IGZ)  
12489 Berlin  
Germany

Phone +49-(0)30-1208820-0  
Telefax +49-(0)30-1208820-90  
Email info@picoquant.com  
Web www.picoquant.com